

1. Identification of the substance and of the company	* Identification of the substance: W, WL10, WL15, WL20, WC20, WVM, WVMW, WK, WLZ * Use of the substance: products such as for lighting- and welding technology, components for high temperature furnace construction, quartz glass production, ion implantation, thin film technology, medical applications * Company: Heeger Materials Inc, 230 Steele St Denver, CO 80206, United States, e-mail: sales@heegermaterials.com *Emergency number: phone +43 (5672)600-0
2. Hazards Identification	* Classification: not hazardous material pursuant to Regulation (EC) no. 1272/2008 EC or EC Directive 67/548/EEC *Compact Metal / Alloy with no Risk to Human Health or the Environment.
3. Composition/Information on ingredients	* Summary: tungsten, addition of oxides of La, Zr and Ce, Al- and K-silicate, < 3 % mass fraction EC no. 231-143-9 CAS no. 7440-33-7 * Hazardous components: none
4. First-aid measures	* Inhalation: no exposure when used as directed. *Skin contact: wash dust off thoroughly with soap and water. * Doctor is needed or advisable: consult a physician after prolonged exposure to dust.
5. Fire-fighting measures	* Suitable extinguishing media: The product itself is not flammable. *Adapt extinguishing measures to surroundings. *Special hazard: increased fire hazard during dust formation. *Protective equipment: breathing protection in the presence of dust.
6. Accidental release measures	* Personnel-related precautionary measures: dust should be suction cleaned directly at source. * Environmental protection measures: no particular environmental protection measures are required.
7. Handling and storage	* Handling: Avoid dust formation. Use suction cleaning if unavoidable and when processing at high temperatures (sublimate formation, see item 10). *Storage: no special measures required.
8. Exposure controls/personal protection	* Exposure thresholds: workplace: 5 mg/m ³ inhalable fraction, mean daily value *Dust-like emissions: General 5 mg/m ³ *Wastewater emissions: 5 mg/l *Workplace exposure: install suction cleaning when working with dust and sublimate and use at least one FFP2 respirator. *Environmental exposure: install suction cleaning with filter when working with dust formation. *Do not empty into drains.
9. Physical and chemical properties	* Appearance: solid grey material *Melting point: 3410 °C *Density: 19,3 g/cm ³ at 20°C *Solubility: insoluble in water, acids and bases; soluble only in hydrofluoric acid or a base in combination with a strong oxidizing agent.
10. Stability and reactivity	* Conditions to be avoided: high temperatures in air (strong oxidation beginning around 400°C, sublimation of WO ₃ beginning around 850°C). * Substances to be avoided: none
11. Toxicological information	* No known toxic effects.
12. Ecological information	* Ecotoxicity: No known ecotoxic effects. *Mobility: low mobility due to low solubility. *Persistence and degradability: stable inorganic material. *Bioaccumulation potential: no evidence of bioaccumulation potential.
13. Disposal considerations	* Dispose of residues as metal waste. *Obey national or regional regulations.
14. Transport information	* ADR / RID / ADN / IATA (ICAO) / IMDG: not a dangerous good pursuant to international transport regulations.
15. Regulatory information	* No labeling required. *The exposure thresholds given under item 8 pertain to Austrian legal regulations. * Obey national regulations.
16. Other information	* Above information corresponds to our current state of knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. * Detailed results of the toxicological and ecotoxicological effects are described in the chemical safety report for REACH registration

Information about the content

Prepared/Updated:	Heeger Materials Inc.
Released:	Heeger Materials Inc.
Valid from:	12-Jul-2022